

AMENDMENTS TO CLAIMS

Claims 1-13 (Cancelled)

14. (Currently amended) The information storage device of claim 18

[13], wherein each first magnetic tunnel junction includes a first sense layer and a first pinned layer; and wherein each second magnetic tunnel junction includes a second sense layer and a second pinned layer.

15. (Currently amended) The information storage device of claim [13]

18, wherein the sense layers of the series-connected junctions are connected in series; and wherein the series-connected sense layers are separated by a layer of non-magnetic material.16. (Currently amended) The information storage device of claim 13, An information storage device comprising:an array of memory cells; anda plurality of first and second traces for the array, the first and second traces extending in different directions;each memory cell being at a cross point of a first trace and a second trace;
at least some of the memory cells including series-connected first and second magnetic tunnel junctions, sense layers of the first and second junctions having different coercivities, wherein the series-connected magnetic tunnel junctions [have] having shared pinned layers.

S.N. 10/697,172

-2-

17.(Currently amended) The information storage device of claim [13]

18. wherein hysteresis loops of series-connected junctions are nested.

18. (Currently amended) [The] An information storage device comprising:

of claim 13;

an array of memory cells; and

a plurality of first and second traces for the array, the first and second traces extending in different directions;

each memory cell being at a cross point of a first trace and a second trace;
at least some of the memory cells including series-connected first and
second magnetic tunnel junctions, sense layers of the first and second junctions
having different coercivities and wherein the sense layers in the series-connected
first and second junctions have different shapes.

19.(Currently amended) The information storage device of claim [13]

18, wherein the sense layers in the series-connected first and second junctions have different sizes.

20.(Currently amended) The information storage device of claim [13]

18, wherein the sense layers of the series-connected first and second junctions have different thicknesses.

S.N. 10/697,172

-3-

21. (Currently amended) [The] An information storage device comprising: of claim 13,
an array of memory cells; and
a plurality of first and second traces for the array, the first and second
traces extending in different directions;
each memory cell being at a cross point of a first trace and a second trace;
at least some of the memory cells including series-connected first and
second magnetic tunnel junctions, sense layers of the first and second junctions
having different coercivities, wherein the sense layers of the series-connected first
and second junctions [are] made of different materials.
22. (Currently amended) The information storage device of claim [13]
18, wherein the series-connected first and second junctions have
distinguishably different delta resistances, whereby each memory
cell having series-connected junctions has at least four
distinguishable logic states.

Claims 23-25 (Cancelled)

S.N. 10/697,172

-4-

PAGE 5/7 *RCVD AT 7/14/2004 4:58:19 PM [Eastern Daylight Time]* SVR:USPTO-EFXRF-1/1 * DNIS:8729318 * CSID:949 454 0898 * DURATION (mm:ss):02:14